



A FLEXcon Holdings Company

Alamotape 210.798.1900
6110 Rittiman Road 800.549.9860
San Antonio, TX 78218 alamotape.com

TECHNICAL DATA SHEET

416NMN525 - 416 Nomex® / PET / 416 Nomex®
Class H 180°C Insulation

A flexible composite insulation composed of type 416 Nomex® meta-aramid paper and electrical grade PET film laminated with a high temperature structural adhesive system.

PRODUCT ATTRIBUTES

- Excellent thermal stability and electrical properties
• High tear, tensile, and burst strength
• Excellent moisture and chemical resistance
• UL 1446 180°C recognized insulation system, file E60273

PRODUCT APPLICATIONS

- Slot and phase insulation for motors and generators
• Layer and ground insulation for Class H dry type transformers

Table with 3 columns: PROPERTY, VALUE, TEST METHOD. Rows include NOMINAL THICKNESS, YIELD, DIELECTRIC STRENGTH, TENSILE STRENGTH, GRAVES TEAR STRENGTH, DISSIPATION FACTOR, VOLUME RESISTIVITY, and SURFACE RESISTIVITY.

STORAGE

- Shelf life: one (1) year
• Store in a clean area free from exposure to excessive heat, moisture or direct sunlight (50°F to 80°F).

Product performance will vary in each application and is dependent upon composite construction. Alamotape does not guarantee the replication of this data by third parties. None of the data or statements contained herein is intended to warrant the performance of this product. Data is representative and not intended as a manufacturing specification.