



TECHNICAL DATA SHEET

Alamotape® 5105 Tacky Thermoset

Alamotape® 5105 Tacky Thermoset performs like a Pressure Sensitive Adhesive (PSA) tape at room temperature and cures to a very high strength with heat and pressure. It is B-stage curable to a permanent thermosetting bond. This tape is ideal for bonding parts without the need for clamping or the mess associated with liquid adhesives.

PRODUCT ATTRIBUTES

- Pressure sensitive adhesive allows parts to be joined without clamping
- Excellent bond strength after curing at elevated temperatures
- Storage stability under ambient conditions - no need for refrigeration
- Good penetration into fiberglass scrim and porous materials
- Excellent metal to metal bonding
- No messy application associated with liquid dispensed adhesives
- No need to wait for extended times for green strength to develop as with liquid adhesives

REPRESENTATIVE PHYSICAL PROPERTIES		
PROPERTY	VALUE	TEST METHOD
PEEL ADHESION: PET (2 mil) /SS 15 min: lb/in. (oz/in)	2.5 (40)	PSTC-101
PRESS BOND: 10 mil foil/Steel, lb/in.	15	
LAMINATION CONDITIONS: Temperature (°C) Pressure (psi) Dwell (minutes)	150 30 30	
LAMINATE ADHESION: Q panel to 7 mil Foil (lb/in)	22	
COATING WEIGHT: (GSM)	54	

STORAGE

- Shelf Life: one (1) year
- Store in a clean area free from exposure to excessive heat, moisture, or direct sunlight (44% to 55% relative humidity, 50°F to 80°F).

Product performance will vary in each application and is dependent upon composite construction. Alamotape does not guarantee the replication of this data by third parties. None of the data or statements contained herein is intended to warrant the performance of this product. Data is representative and not intended as a manufacturing specification.